

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S1	9587	((257/434,673,680,704,782,672,676,684,777,788,666,673) or (438/121,123,380,377) or (174/52.3,52.4)).CCLS.	US-PGPUB; USPAT; EPO	OR	OFF	2004/12/06 11:28
S2	127	S1 and metal adj wiring	US-PGPUB; USPAT; EPO	OR	ON	2004/12/06 11:35
S4	1	"20020105591"	US-PGPUB; USPAT; EPO	OR	ON	2004/12/06 15:38
S5	97	S1 and frame adj base	US-PGPUB; USPAT; EPO	OR	ON	2004/12/06 12:00
S7	223	"257"/\$.ccls. and frame adj base	US-PGPUB; USPAT; EPO	OR	ON	2004/12/06 12:02
S8	135	S7 not S5	US-PGPUB; USPAT; EPO	OR	ON	2004/12/06 12:02
S9	9587	((257/434,673,680,704,782,672,676,684,777,788,666,673) or (438/121,123,380,377) or (174/52.3,52.4)).CCLS.	US-PGPUB; USPAT; EPO	OR	OFF	2004/12/06 15:38
S10	14	S9 and transparent with between with wire	US-PGPUB; USPAT; EPO	OR	ON	2004/12/06 16:42
S12	9	("4442456" "5321204" "5357056" "5534725" "5773323" "5786589" "5952714" "6040612" "6071760").PN.	US-PGPUB; USPAT; USOCR	OR	ON	2004/12/07 16:16
S13	116	anisotropic with sealing with material	US-PGPUB; USPAT; USOCR	OR	ON	2004/12/06 16:56
S14	4938	((348/294,373,374) or (257/434,678,687-690)).CCLS.	US-PGPUB; USPAT; EPO	OR	OFF	2004/12/07 16:17
S15	145	S14 and solid adj state adj2 sens\$3	US-PGPUB; USPAT; EPO	OR	ON	2004/12/07 16:18